# MOBILE PC WORKSTATIONS 4 TYPES 10 COLOURS



### **TECHNICAL SPECIFICATION**

### STANDARD MODULE





Compartment with option to add pull-out shelves and height-adjustable shelves, to accommodate hardware equipment and printers.

Usable Width: 663 mm Usable height: 754 mm 2 fixed wheels and 2 swivel castors with ø 100 mm nylon brake





### **DOOR MODULE**

Security lock and polycarbonate glass. Working dimensions: 655x465 mm H.



Possible addition of a monitor up to 21". Inside dimensions of the top compartment: 710x530 mm H.

### **SHUTTER MODULE**

Ideal for touch screens.
Usable dimensions: 660x525 mm H.

Security lock and plastic shutter with ergonomic handle

Extensible drawer with keyboard shelf 2 opening locking positions rear space for item storage

Usable dimensions: 655x465 mm H

THE MODULES WITH **DOOR** AND **SHUTTER** ARE DESIGNED TO LET THE MONITOR POWER CABLE THROUGH BY PROVIDING A GAP BETWEEN THE SUPPORT SHELF AND THE REAR WALL.





# PERFORATED PANEL MODULE WITH 3 EDGE TOP COVERED IN PVC

Made of sheet steel with holes for tool/Practibox hooks see page 102





METAL COLOURS  $\sqrt{\phantom{a}}$ 





RAL 7000 .01



RAL 6011 .02



RAL 5012 .04





GREY RAL 7035 .08



GREY WHITE RAL 9002 .1F



RAL 3003 .1G



GENTIAN BLUE RAL 5010 .34



PURE WHITE RAL 9010 .35



RAL 7016 .39



BLUE CAPRI RAL 5019 .48

PLASTIC parts colour range



DARK GREY .M0

CABINET CAPACITY 100 kg



KEY LOCK (KEY) The cylinder closure "C0" is supplied as standard in cabinets. "C1" or "C2" versions on request. See Master section page 31

**KEY** 









ALL INDICATED LOAD CAPACITY VALUES ARE NET AND REFER TO EVENLY DISTRIBUTED WEIGHTS





Standard cabinet with wheels complete with DOOR MODULE with polycarbonate glass, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf

Overall dimensions mm791x598x1735 H



Standard cabinet with wheels, 1 drawer with keyboard shelf, 3-edge top shelf coated in PVC, 1 adjustable middle shelf, 1 extensible shelf

Overall dimensions mm 791x598x1104 H




2 nylon fixed wheels Ø 100 mm 2 nylon swivel wheels with brake Ø 100 mm

### H 1731 mm



Standard cabinet with wheels complete with SHUTTER MODULE, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf Overall dimensions mm 791x598x1735 H

### H 1800 mm



Standard cabinet with wheels complete with PERFORATED PANEL, 3-edge top shelf coated in PVC, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf Overall dimensions mm 791x598x1800 H



ELECTRICAL SYSTEM AND FAN NOT INCLUDED TO COMPLETE YOUR CABINET GO TO PAGE 523



MODULES WITH POLYCARBONATE GLASS DOORS WITH SHUTTER AND PERFORATED PANEL ARE NOT INSTALLED ON STANDARD MODULES. SUPPLIED AS STANDARD WITH FIXING MATERIAL.

# CONFIGURE YOUR CABINET





Drawer equipped with gray RAL 7035 painted top for keyboard.

### STANDARD MODULE WITH WHEELS

ART.	V	k9	<b>=</b>	2
F AS 1400	01	50-75-100	100-96-92%	key

### CABINET WITH HINGED DOORS

Complete with 2 external grids with dust filter, plate with outlet holes for network cables and electrical system cables, side handle, drawer with keyboard shelf, top hole with black plastic cable guide, pair of plates with 2 nylon fixed wheels and 2 nylon swivel wheels with brake  $\varnothing$  100 mm. Overall dimensions mm 791x598x1081 H

Usable dimensions: 663x754 mm H

### **LOCKS SEE PAGE 31**







MODULES DOORS WITH POLYCARBONATE GLASS WITH SHUTTER AND PERFORATED PANEL DO NOT BE MOUNTED TO THE STANDARD MODULE. SUPPLIED SERIES WITH FIXING MATERIAL.









## **COMPONENTS**



### SHUTTER MODULE

ART.	V	
F AS 1450	20	key

Dimensions: 714x247x650 mm H Usable dimensions: 655x215x465 mm H

Including with screws for fixing to the standard module



### DOOR MODULE WITH POLYCARBONATE GLASS

ART.	V	
F AS 1450	10	key

Dimensions: 714x247x650 mm H
Usable dimensions: 660x215x525 mm H

Including with screws for fixing to the standard module

THE MODULES WITH DOOR AND SHUTTER CAN BE USED INDEPENDENTLY ON WORK BENCHES OR WORK STATIONS.



### PERFORATED PANEL

ART.	dim. mm
M 30 PA71 00 00 00	708x65x718 H



### ART. M 00 PA71 00 00 F1 00

DRILLED TOP SHELF WITH 3/4 EDGES FOR PERFORATED PANEL FIXING - INCLUDING SCREWS



### **3-EDGE TOP SHELF**

ART.	dim. mm	
M 32 T023 AG 00 31 07	714x573x23 H	

PVC coated shelf. Colour black



ART. M 00 T023 AG 00 F1 00 3-EDGE DRILLING FOR CABLE PASSAGE



Cable length 2 m Complete with spare plate galvanised finish

### MULTIPLE MOBILE SOCKET, 4 UNIVERSAL SOCKETS, MAX POWER 3680 W

ART.

F AS 4000 01 00

### MULTIPLE MOBILE SOCKET 2P + E 16 A 250 V $\,\sim\,$

- 4 universal sockets max power 3680 W for:
 European plugs 2P 2.5 A
 Italian standard plugs 2P and 2P + E 10 A and 16 A
 German standard plugs 2P + E 16 A
 American standard 2P plugs with flat prongs 15 A 125 V non-polarised

- 2 m of 3G 1 mm cable and plug 2P+T 16 A 250 V  $\sim$  German standard (Schuko) note: no grounding connection on the 2P + E 16 A 250 V  $\sim$  French standard

### REGULATORY COMPLIANCE

Standard CEI 23-124

### 5 OUTLET MULTIPLE MOBILE SOCKET





### MULTIPLE MOBILE SOCKET 220–250V $\sim$ 10A 2P+E:

- 230V~ 10A magnetothermal cutoff switch
- 5 220-250V~ 10A 2P+E sockets (see table)
- 1 220-250V~ 16A 2P+E industrial plug DEGREE OF PROTECTION IP 30

### REGULATORY COMPLIANCE

Standard CEI EN 60204-1:

- equipotential protection circuit continuity applied voltage
- insulation resistance



Cable length 3,5 m Complete with spare plate galvanised finish



# **ACCESSORIES**



### SPARE PLATE GALVANISED

ART.	dim. mm	
F AS 3021 00 99	550x10x67 H	



### **FAN**

ART.

F AS 3220 01 00

220V fan wired without grid with Schuko plug



### **PROFILE**

ART.

F AS 4000 PC 07

4-way plastic cable guide, 1000 mm long

